Fisher TEXTILES
the fabric of success



TECHNICAL DATA SHEET

GF 6050 SUPER SONIC BACKLIT (FR)

WEIGHT:	7.7 oz/yd^2 (260 g/m^2)
WIDTH:	126″
COMPOSITION:	100% Polyester
CONSTRUCTION:	Knit
PRINTING COMPATIBILITY:	Dye Sub Transfer
PRINT SIDE:	Suede side, typically wound out.

BACK/FACE:



FLAME RETARDANCY:	NFPA-701; California Administrative Code Title 19 - Public Safety, Section 1237; Registered in the State of California (CSFM Registration Number: F-100615) and meets Section 13115 of the California Health and Safety Code; ASTM E 84-21: Meets Class A, Flame Spread Index 25 or less and Smoke Developed Index 450 or less
TRANSFER CONDITIONS:	400°F 35 P.S.I. 45-60 Seconds
STRETCH (ASTM D2594):	Length: 3.2% Width: 4.8%
THICKNESS (ASTM D1777):	0.61 mm
SPECIAL FEATURES:	This fabric is foldable, offering a savings on finished product shipping costs. Direct print, 5-meter-wide version also available.
DURABILITY:	Dependent upon the environment the fabric is exposed to.
SUGGESTED APPLICATIONS:	Backlit, Exhibit Graphics, Retail Displays, Silicone Edge Graphics

The above recommendations are a result of laboratory testing. We recommend additional testing in the manufacturing facility prior to printing. Data are averages achieved for actual production runs. Product safety evaluations may not have been completed for the intended use. Samples of this product should be used for concept evaluations only.

Revised: 6.17.2022

Fisher Textiles | 4211 Matthews Indian Trail Road, Matthews, NC 28104
Toll Free: 800.554.8886 | Fax: 704.821.8880 | fishertextiles.com |